



AMACO METAL ENAMELING KILN COMPARISON CHART

Kiln Model Photos are shown to scale for size comparison	Maximum Recommended Temperature	Firing Chamber Area	Chamber Size	Exterior Dimensions	Kiln Weight	Shipping Weight (approximate)	Furniture Kit
62-EFC 	Cone 03 2019°F 1104°C	238.5 cubic inches 3908.31 cubic centimeters	6 ³ / ₈ " w 7 ⁷ / ₈ " d 4 ³ / ₄ " h 16.19cm w 20cm d 12.07cm h	14 ⁵ / ₈ " w 16 ³ / ₄ " d 17 ¹ / ₂ " h 37.15cm w 42.55cm d 44.45cm h	37 lbs. 16.78 Kg	47 lbs. 21.32 Kg	Kiln Shelf 6" x 6" x 1/2", ▲ 06 11346A \$8.95 SSU=1, Shipping Weight 1 lb.
67-EFC 	Cone 03 2019°F 1104°C	675 cubic inches 11061.27 cubic centimeters	10" w 13 ¹ / ₂ " d 5" h 25.4cm w 34.29cm d 12.7cm h	18 ³ / ₄ " w 22 ¹ / ₂ " d 18 ⁵ / ₈ " h 47.63cm w 57.15cm d 47.31cm h	67 lbs. 30.39 Kg	80 lbs. 36.29 Kg	Kiln Shelf 9" x 9" x 1/2", ▲ 06 11348C \$14.95 SSU=1, Shipping Weight 3 lbs.

*** WIDTH DIMENSION INCLUDES SELECT FIRE™.**

▲ Cone number specifies maximum temperature for shelves



METAL ENAMELING KILN COMPARISON CHART

Kiln Vent	Kilowatt Rating	Electrical Requirements	Supplied Power Cord	Amperage Rating	Kiln with Kiln-Sitter® and Timer Single Phase	Kiln with Kiln-Sitter® and Timer Three Phase	Kiln with Select Fire™ Single Phase	Kiln with Select Fire™ Three Phase	Kiln Model
N/A	1.2	12 Gauge Wire	Cord with grounded 3-prong plug	Single Phase Only: 10.0 @ 120 Volt	Kiln Only Single Phase	Kiln with Pyrometer Single Phase	Not Available with Select Fire™	Not Available with Select Fire™	62-EFC
					120V 27301C \$895.00*	120V 26053H \$1095.00**			
N/A	1.8	12 Gauge Wire	Cord with grounded 3-prong plug	Single Phase Only: 15.0 @ 120 Volt	Kiln Only Single Phase	Kiln with Pyrometer Single Phase	Not Available with Select Fire™	Not Available with Select Fire™	67-EFC
					120V 27321Y \$1095.00*	120V 26087W \$1195.00**			

*PRICE FOR KILN ONLY, WITHOUT PYROMETER.

**PRICE FOR KILN WITH PYROMETER ONLY; SITTING/TIMER NOT AVAILABLE.