

MATERIAL SAFETY DATA SHEET

Product Name: Flexwax 120

Product Code: Flexwax

Manufacturer's Name: American Art Clay Co., Inc.
6060 Guion Road
Indianapolis, IN 46254

Information Number: (800) 374 - 1600

Emergency Number: (800) 374 - 1600

Section I – Product Identification

Product Name: Flexwax 120

Product Class: Craft

Product Size: 2 1/2lbs, 5lbs

Flexwax 120

Section II – Hazardous Ingredients

Reportable Components

CAS#

Vapor Pressure
Mm Hg @ Temp

Weight
Percent

No report hazardous ingredients.

This product carries the “AP” Seal. Labeling conforms to ASTM D-4236.

Section III – Physical / Chemical Characteristics

Boiling Range: NA

Specific Gravity (H20=1): Less than 2.

Vapor Density: Heavier than air.

Evaporation Rate: NA

Coating V.O.C.: NA

Material V.O.C.: NA

Appearance & Odor: Solid block.

Section IV – Fire and Explosion Hazards

Flash Point: NA

Method Used: NA

Flammable Limits in Air by Volume: NA – Lower

NA – Upper

Extinguishing Media: Foam, CO2, and Dry Chemical Water Fog

Special Firefighting Procedures: Use fire extinguisher – suitable for wax.

Unusual Fire and Explosion Hazards: Keep away from heat, sparks, and open flame.

Section V – Reactivity Data

Stability: Stable

Conditions to Avoid: Open flame

Incompatibility (Materials to Avoid): None.

Hazardous Decomposition or Byproducts: Will not occur.

Hazardous Polymerization: Will not occur.

Section VI – Health Hazards

Inhalation Health Risks and Symptoms of Exposure: Molten wax fumes cause mild (upper) respiratory irritation.

Skin and Eye Contact health Risks and Symptoms of Exposure: Eye – Molten fumes may be slightly irritating to eyes. Skin – molten wax will cause burns on contact.

Skin Absorption Health Risks and Symptoms of Exposure: See above.

Ingestion Health Risks and Symptoms of Exposure: No hazardous ingredients.

Health Hazards (Acute / Chronic): See above.

Carcinogenicity: No – NTP Carcinogen No – IARC Monographs No – OSHA Regulated

Medical Conditions Generally Aggravated by Exposure: Unknown.

Emergency and First Aid Practices: Contact you local poison control for further health information.

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken In Case Material Released or Spilled: Uncontaminated material may be salvaged and used. If contaminated, dispose.

Waste Disposal Method: Dispose of in trash. In manufacturing, dispose of in accordance to Local, State or Federal regulations.

Precautions to Be Taken in Handling and Storing: Store away from open flame.

Other Precautions: **Wax melting should be done by adult.** Temperature of melted wax should be measured with a thermometer and kept at 120°F in order to prevent breakdown of wax or risk of skin burns.

Section VIII – Control Measures

Respiratory Protection: Adequate cross ventilation necessary due to vapors.

Ventilation: Adequate cross ventilation due to vapors.

Protective Gloves: Not needed.

Eye Protection: Not needed.

Other Protective Clothing or Equipment: Not needed.

Work / Hygienic Practices: Refer to AMACO Product Encyclopedia & Safety Manual.

Section IX – Disclaimer

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control we make no warranties, expressed or implied, except for those that may be contained in our written acknowledgement.

Prepared by: L. Jenkins
2009